



Μεγ. Λαύρας 15 Μουρνιές Χανίων

Τηλ. 28210 36278 fax 28210 36289

«Προμήθεια ανταλλακτικών του Συστήματος Παρακολούθησης, Ελέγχου και Συλλογής Δεδομένων -SCADA- της Εγκατάστασης Επεξεργασίας Λυμάτων -ΕΕΛ- Χανίων»

ΠΡΟΣΦΟΡΑ

Του

Έδρα

Οδός Αριθμός

Τηλέφωνο

Fax : e-mail :

ΚΩΔΙΚΟΣ	ΠΕΡΙΓΡΑΦΗ	ΠΟΣΟΤ.	Τ. ΜΟΝ*	ΣΥΝΟΛΟ
6ES71316BH002BA0	SIMATIC ET 200SP, Digital input module, DI 16x 24V DC Standard, type 3 (IEC 61131), sink input, (PNP, P-reading), Packing unit: 1 Piece, fits to BU-type A0, Colour Code CC00, input delay time 0,05..20ms, diagnostics wire break, diagnostics supply voltage	5		
6ED1052-1CC08-0BA0	LOGO! 24CE, logic module, Display PS/I/O: 24 V/24 V/24 V trans., 8 DI (4AI)/4DO, memory 400 blocks, modular expandable, Ethernet integr. web server, data log, user defined Web pages, standard microSD card for LOGO! Soft Comfort V8 or higher, older projects executable	2		
6ED1055-1CB10-0BA2	LOGO! DM16 24 expansion module, PS/I/O: 24 V DC/24 V DC/trans., 8 DI/8 DO, 4 MW for LOGO! 8	2		
6EP13321SH71	SIMATIC S7-1200 POWER MODULE PM1207 STABILIZED POWER SUPPLY INPUT: 120/230V AC OUTPUT: 24 V DC/2.5 A	1		
6EP13332BA20	SITOP PSU100S 24 V/5 A STABILIZED POWER SUPPLY INPUT: 120/230 V AC OUTPUT: 24 V/5 A DC	3		
6ES7 404-0KA02-0AA0	SIMATIC S7-400, POWER SUPPLY PS407: 10A, WIDERANGE, 120/230V UC, 5V DC/10A	1		
6ES7132-6BH01-0BA0	SIMATIC ET 200SP, Digital output module, DQ 16x 24V DC/0,5A Standard, Source output (PNP,P-switching) Packing unit: 1 piece, fits to BU-type A0, Colour Code CC00, substitute value output, module diagnostics for: short-circuit to L+ and ground, wire break, supply voltage	7		

ΚΩΔΙΚΟΣ	ΠΕΡΙΓΡΑΦΗ	ΠΟΣΟΤ.	T. ΜΟΝ	ΣΥΝΟΛΟ
6ES7134-6HB00-0DA1	SIMATIC ET 200SP, Analog input module, AI 2x U/I 2-4-wire High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.3%	5		
6ES7135-6HB00-0DA1	SIMATIC ET 200SP, Analog output module, AQ 2x U/I High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.2%	3		
6ES7138-4HA00-0AB0	SIMATIC DP, DP master interface for IM151-7 CPU or IM151-8 PN/DP (ET200S), module with PROFIBUS DP interface (9-pole D-sub socket) as DP master	2		
6ES7151-7AA21-0AB0	SIMATIC DP, IM151-7 CPU for ET200S, 128 KB work memory with integrated PROFIBUS DP interface (9-pole D-sub socket) as DP slave, without battery SIMATIC MMC required	2		
6ES7153-1AA03-0XB0	SIMATIC DP, Connection IM 153-1, for ET 200M, for max. 8 S7-300 modules	5		
6ES7155-6BA00-0CN0	SIMATIC ET 200SP, PROFIBUS bundle IM, IM 155-6DP HF, max. 32 I/O modules and 16 ET 200AL modules, multi hot swap, bundle consists of: Interface module (6ES7155-6BU00-0CN0), server module (6ES7193-6PA00-0AA0), PROFIBUS connector (6ES7972-0BB70-0XA0)	3		
6ES72141AG400XB0	SIMATIC S7-1200, CPU 1214C, COMPACT CPU, DC/DC/DC, ONBOARD I/O: 14 DI 24V DC; 10 DO 24 V DC; 2 AI 0 - 10V DC, POWER SUPPLY: DC 20.4 - 28.8 V DC, PROGRAM/DATA MEMORY: 100 KB	1		
6ES72211BH320XB0	SIMATIC S7-1200, DIGITAL INPUT SM 1221, 16 DI, 24VDC, SINK/SOURCE INPUT	2		
6ES7312-1AE14-0AB0	SIMATIC S7-300, CPU 312 Central processing unit with MPI, Integr. power supply 24 V DC, Work memory 32 KB, Micro Memory Card required	3		
6ES7321-1BH02-0AA0	SIMATIC S7-300, Digital input SM 321, isolated, 16 DI, 24 V DC, 1x 20-pole	10		

ΚΩΔΙΚΟΣ	ΠΕΡΙΓΡΑΦΗ	ΠΟΣΟΤ.	T. MON	ΣΥΝΟΛΟ
6ES7321-1BL00-0AA0	SIMATIC S7-300, Digital input SM 321, Isolated 32 DI, 24 V DC, 1x 40-pole	2		
6ES7322-1BH01-0AA0	SIMATIC S7-300, Digital output SM 322, isolated, 16 DO, 24 V DC, 0.5A, 1x 20-pole, Total current 4 A/group (8 A/module)	7		
6ES7331-7KB02-0AB0	SIMATIC S7-300, Analog input SM 331, isolated, 2 AI, Resolution 9/12/14 bits, U/I/thermocouple/resistor, alarm, diagnostics, 1x 20-pole, Removing/inserting with active backplane bus	2		
6ES7331-7KF02-0AB0	SIMATIC S7-300, Analog input SM 331, isolated, 8 AI, Resolution 9/12/14 bits, U/I/thermocouple/resistor, alarm, diagnostics, 1x 20-pole Removing/inserting with active backplane bus	13		
6ES7332-5HD01-0AB0	SIMATIC S7-300, Analog output SM 332, isolated, 4 AI, U/I; diagnostics; resolution 11/12 bits, 20-pole, removing and inserting possible with active backplane bus	5		
6ES7360-3AA01-0AA0	SIMATIC S7-300, Connection IM 360 in central rack for connection of max. 3 expansion racks, with C-bus	2		
6ES7414-2XL07-0AB0	SIMATIC S7-400, CPU 414-2 Central processing unit with Work memory 2 MB, (1 MB code, 1 MB data), 1st interface MPI/DP 12 Mbit/s, 2nd interface PROFIBUS DP	1		
6ES74217DH000AB0	SIMATIC S7-400, SM 421 DIGITAL INPUT MODULE, OPTIC. ISOLATED, 16 DI, 24 - 60V UC, ALARM, DIAGNOSTICS	1		
6ES74601BA010AB0	SIMATIC S7-400, IM460-1 TRANSMITTER INTERFACE MODULE, FOR CENTRALIZED CONNECTION WITH PS TRANSMISSION W/O K BUS	1		
6ES79710BA00	SIMATIC S7-400, BACK-UP BATTERY 3.6 V/2.3 AH FOR PS 405 4A/10A/20A AND PS 407 4A/10A/20A	6		
6ES7972-0BB12-0XA0	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90B° cable outlet, 15.8x 64x 35.6 mm (WxHxD), terminating resistor with isolating function, With PG receptacle	5		

ΚΩΔΙΚΟΣ	ΠΕΡΙΓΡΑΦΗ	ΠΟΣΟΤ.	T. ΜΟΝ	ΣΥΝΟΛΟ
6GK1500-0EA02	PROFIBUS bus onnector with axial cable outlet for Industry PC, SIMATIC OP, OLM; Transmission rate 12 Mbit/s; terminating resistor with isolating function, Metal enclosure	5		
6GK7342-5DA03-0XE0	Communications processor CP 342-5 for connection of SIMATIC S7-300 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication	1		
6GT2500-3BF10	MOBY U Mobile data memory MDS U315, 2 KB RAM, replaceable battery, IP65, -25 to +70 °C, 111x 67x 23.5 mm	4		
6ES7392-1AJ00-0AA0	SIMATIC S7-300, Front connector for signal modules with screw contacts, 20-pole	10		
6ES7392-1AM00-0AA0	SIMATIC S7-300, Front connector with screw contacts, 40-pole	10		
	ΑΘΡΟΙΣΜΑ			
	ΦΠΑ 24%			
	ΓΕΝΙΚΟ ΣΥΝΟΛΟ			

132

*Η τιμή, του προς προμήθεια υλικού, δίνεται σε ευρώ ανά μονάδα και θα έχει μέχρι και δύο δεκαδικά ψηφία

Ο προσφέρων θα μονογράψει την κάθε σελίδα και θα υπογράψει την παρούσα που θα φέρει και την σφραγίδα της εταιρείας.

Χανιά / /

Ο ΠΡΟΣΦΕΡΩΝ